

210 CHALLENGER[®] S



Premium helm with Cruise control, Ski mode (twin engine only) and ECO™ mode



Spacious cockpit area



Snap-in carpet



Satellite-ready stereo with USB Direct Control and MP3 port



Speakers



Removable cockpit table

A spacious well-equipped boat at a price that'll seem like the greatest perk of all. Thanks to the features of the S package that include engine options, a bi-fold see-through door, snap-in carpets, rear cockpit table to gather friends and family and a bimini top that you can put up or down at your convenience. Plus get to choose between twin injected engines and a single supercharged high output engine.

ALL-NEW FOR 2012



Glorious Red

HIGHLIGHTS

- Single 1.5 l supercharged high output Rotax® 4-TEC® engine
- Satellite-ready stereo with USB Direct Control, MP3 port, 2 speakers
- iTC™ (Intelligent Throttle Control) – drive by wire
- Chrome cleats (6)
- Cruise control
- ECO mode
- Docking mode
- Ski pylon – removable
- Removable cooler
- Swim platform storage – lockable

S PACKAGE HIGHLIGHTS

- Additional engine option: Twin 1.5 l injected Rotax 4-TEC
- Snap-in carpet
- Cockpit table
- Bimini top
- Bi-fold see-through door
- **ALL-NEW** Weedless system (optional with twin engine only)

SPECIFICATIONS

DIMENSIONS

Length	20' 6" / 6.25 m
Beam	8' 6" / 2.59 m
Draft	12" / 30.5 cm
Dry weight: Single engine	2,925 lb / 1,327 kg
Twin engine	3,100 lb / 1,406 kg
Seating capacity	10 (9) ¹
Fuel capacity	41 gal / 155.2 l (Single engine)
	44 gal / 166.6 l (Twin engine)

ENGINE

Model	1503 Rotax 4-TEC
Type	1.5 l supercharged high output or Twin 1.5 l injected

¹Passenger Capacity: USCG (Transport Canada)



OVERALL SPECIFICATIONS

DIMENSIONS

Length	20' 6" / 6.25 m
Beam	8' 6" / 2.59 m
Draft	12" / 30.5 cm
Dry weight:	Single engine 2,925 lb / 1,327 kg
	Twin engine 3,100 lb / 1,406 kg
Storage capacity	56.65 cu ft / 1.6 cu m
Seating capacity	10 (9) ¹
Weight capacity	1,525 lb / 692 kg
Fuel capacity	41 gal / 155.2 l (Single engine)
	44 gal / 166.6 l (Twin engine)

DIMENSIONS (ON TRAILER)

Length [tongue folded]	23' 6" / 7.16 m [21' 1" / 6.43 m]
Width	8' 6" / 2.59 m
Height:	6' 11" / 2.11 m
Gross weight:	Single engine 3,895 lb / 1,767 kg
	Twin engine 4,070 lb / 1,846 kg

ENGINE

Model	Fuel injected, 1503 Rotax 4-TEC
Displacement	1,494 cc
Type:	Single 1.5 l supercharged high output
	Twin 1.5 l injected
Cylinders (/engine)	3
Max RPM (/engine):	1.5 l injected 7,300
	1.5 l supercharged high output 8,000
Fuel type:	1.5 l injected 87 octane
	1.5 l supercharged 87 octane – minimum
	91 octane – recommended
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System

EQUIPMENT

HULL & DECK

- Cleats – chrome (6)
- Cup holders (10)
- Rub rail
- Grab handles (7)
- Navigation lights
- Courtesy lights (3)
- Ski pylon – removable
- Tow hooks bow & stern – stainless steel
- Ski eye – stern
- Walk-through – bow & stern
- Reboarding ladder – stern (2-step)
- Engine blower (2)
- Automatic bilge pump

STORAGE

- Anchor locker
- In-floor, lockable
- Console – port & starboard
- Under seat
- Glove box
- Cargo net
- Swim platform, lockable

CONTROL STATION

HELM

- Steering – standard
- Steering – tilt, rack & pinion (twin engine only)
- Horn
- Shift & throttle lever – chrome
- Neutral lock
- Intelligent throttle control
- Battery switch
- Circuit breakers
- Engine synchronization (twin engine only)

CONTROL STATION (CONT.)

INSTRUMENTATION

- Gauges – backlight & anti-fog
- Fuel level
- Fuel consumption meter
- ECO mode
- Tachometer
- Speedometer
- Hour meter
- Maintenance info
- Compass
- Cruise control
- Docking mode
- Ski mode (twin engine only)
- Low fuel level
- Low oil level
- Low oil pressure
- Low voltage
- Overheat
- Hi voltage
- Check engine
- Sensor check
- Battery protection

STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – cockpit (2)
- MP3 port
- USB direct control

ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Deadrise	21°
Graphics	Std
Colors:	Riviera Blue
	Glorious Red

PROPULSION

Jet pump type	Axial flow	Single stage
iTC – Intelligent throttle control		Std
Impeller:	Material	Stainless steel
	Outside diameter (mm) 1.5 l injected	155 ± .07
	1.5 l supercharged high output	161 ± .07
Reverse system		Std

COCKPIT

- Carpet – snap-in
- Dash finish – silver/chrome
- Outlet – 12 volt accessory (2)
- Cooler – removable
- Table
- Table mount – cockpit and bow and swim platform

SEATING

- Driver Seat
- Track & swivel
- Bolster
- Passenger Seat
- Track & swivel
- Bolster

CANVAS & MISCELLANEOUS

- Bimini top
- Bi-fold see-through door
- Windshield – fixed
- Warranty (1 yr)

CERTIFICATIONS

- NMMA
- CMMA

TRAILER^o

- Tandem axle
- Single disc brake
- Swing-away tongue

210 CHALLENGER S

