



2017 PERFORMANCE **GTR™-X® 230**

New for 2017! The GTR-X is the most affordable Sea-Doo X model. Enjoy the unmatched control of the Ergolock system and a new and powerful supercharged 230-hp Rotax engine. This watercraft accelerates from 0-60 mph (0-96 in 5.29 seconds).



RIDER CAPACITY

2

Weight capacity 400 lb / 182 kg

DIMENSIONS

Fuel capacity 15.9 US gal / 60 l
 Length 130.6" / 331.6 cm
 Width 48.5" / 123.1 cm
 Weight (dry) 821 lb / 373 kg
 Storage capacity 30.7 US gal / 116.4 l

HULL

Type GTI
 • Medium-sized platform
 • Moderate V hull
 • Forgiving and nimble

ENGINE

Type Rotax 1500 HO ACE
 Intake system Supercharged with external intercooler
 Displacement 1,494 cc
 Cooling Closed-Loop Cooling System (CLCS)
 Reverse system Electronic iBR®
 Starter Electric
 Fuel type 87 octane

California Green Metallic & Black ab

iTC / iBR / CLCS / ECO



ROTAX® 1500 HO ACE™ ENGINE



ERGOLOCK™ SYSTEM



HIGH-PERFORMANCE VTS™ (VARIABLE TRIM SYSTEM)



X-GAUGE WITH BOOST INDICATOR



RXP-X AWARD-WINNING DESIGN



SNAP-IN FENDERS AND INSTALLATION KIT (OPTION)

GTR-X 230

ENGINE

1,494 cc four-stroke, Rotax with three cylinders in-line and four valves per cylinder

Equipped with Advanced Combustion Efficiency (ACE) technology, this new engine with maintenance-free supercharger and external intercooler is optimized for regular fuel, faster and more powerful than its predecessor, but just as fuel efficient.

iTC™ (Intelligent Throttle Control) system

Operating electronically, this advanced throttle system starts you in neutral for easier dockside starts. It also features activity-specific Touring, Sport and ECO™ modes that can all be set to accommodate your riding style. The result is a more responsive, more intuitive ride.

iControl® Learning Key®

The programmable Learning Key allows you to limit the performance of the PWC based on rider skill-level.

D-Sea-Bel™ system

Combines a series of resonators and vibration-absorbing components to make Sea-Doo watercraft some of the quietest on the water.

Closed-Loop Cooling System

Uses coolant to keep the engine running at the ideal temperature, much like a car's radiator. Also keeps out corrosive saltwater and debris.

FEATURES

iControl

The "Brain" that integrates and controls all systems to create the best possible ride.

Touring mode / Sport mode

Offers a choice between two throttle responses for different riding styles. Touring mode is the default setting offering a more progressive acceleration curve for a more confident ride – ideal for cruising and 2-up riding. Sport mode can be easily activated using the Sport button. It provides all acceleration performance for a more aggressive throttle response.

ECO mode

This iTC function automatically determines the most economical power delivery and sets the optimal RPM for greatest fuel economy.

Ergolock system

Combination of ergonomic features allow amazing control while cornering with less upper body fatigue. It features a narrow racing seat with knee grab design, adjustable handlebars and angled footwells that allow you to "lock in" when cornering hard. This results in faster turns and more time on the water.

High-performance VTS (Variable Trim System)

The VTS adjusts the angle of the nozzle to change the behavior of the watercraft and improve parallelism to the water. The high-performance VTS provides pre-set positions for quick settings.

RF D.E.S.S.™ Key

With radio frequency technology and a ball-and-socket design, the Digitally Encoded Security System (D.E.S.S.) key provides riders with easy and quick starts every time.

Interactive Multifunction Digital Information Center

VTS preset, Fuel consumption instant & average, Fuel level, Tachometer, Speedometer, Hour meter, Compass, Clock, Touring mode, Sport mode, ECO mode, F-N-R indicator and more.

Handgrips with palm rest

Seat strap

Sponsons

Elevated fuel filler

Bumpers

Front splash deflector

Wide-angle mirrors

Dual drain plugs

Tow hook

Flush kit

Footwell carpets with Sea-Doo logo pattern

Emergency floating lanyard

Swim platform carpet with Sea-Doo logo

Operator's guide, instructional video and booklet

Rear grab handle



PROPULSION SYSTEM

iBR (Intelligent Brake & Reverse) system

First and only true brake on a watercraft recognized by the U.S. Coast Guard for improving boating safety since 2009. Now in its 2nd generation, the intuitive and improved iBR allows you to stop close to 160 feet sooner¹ for greater peace of mind. All with the squeeze of a lever. And with its electronic reverse, it gives you a level of maneuverability that makes docking easier.

Stainless steel impeller

Delivers improved acceleration, higher top speed and less cavitation.

X PACKAGE

X-Handlebars with A.E.S.™ (Adjustable Ergonomic Steering)

The only fully adjustable handlebar in the industry. With A.E.S. the rider can adjust the handlebar width and grip angle for a fully customized ride.

X-Gauge with boost indicator

Shows the boost pressure in real-time from minimum (idle) to max boost pressure (open throttle) at all times so the rider knows the engine load condition.

Additional gauge functions

Time / Distance to empty, Top / average speed / RPM, Lap timer, Engine temperature.

X-Coloration

OPTIONS

Reboarding Ladder

Depth Finder

Sea-Doo Speed Tie™

Dry Bag

Front Storage Tray

12-Volt Outlet and Installation Kit

Safety Equipment Kit

Bilge Pump Kit

Sandbag Anchor

Fire Extinguisher

Snap-in Fenders and Installation Kit

Sea-Doo Move Trailer

Watercraft Cover

WARRANTY

BRP limited warranty covers the watercraft for one year.



©2016 Bombardier Recreational Products Inc., (BRP). All rights reserved.™, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. Products are distributed in the USA by BRP US Inc. Performance number in metric horsepower achieved under optimal testing conditions. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Printed in Canada.

¹Based on BRP internal testing.

SEA-DOO

